

Carrier 38 RA 100-A0029-PEE Condensing unit

Specifications

Brand	Carrier
Туре	38 RA 100-A0029-PEE
	Condensing unit
Product type	Air Cooled Chiller
Capacity kW	95,0
Capacity Tons	27,0
Refrigerant	Freon
Refrigerant Type	407C
Weight in kg.	1108
Sizes	2270x2060x1450 mm
	(LxWxH)
Compressor(s) type &	(x1) Performer
model	SZ185S4CC & (x1)
	Performer SZ 115S4CC &
	(x1) Performer
	SZ160T4CC
Number of fans	2
Remarks	Y.o.b. 2005
Stock	2



Description

Used Carrier 38 RA 100-A0029-PEE Condensing unit

Used Carrier 38 RA 100 air cooled condensing unit. Complete with 3 Performer scroll compressors: (x1) Performer SZ185S4CC & (x1) Performer SZ 115S4CC & (x1) Performer SZ160T4CC. Condensor with 2 axial fans with a total airflow of 7950 l/s. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.

www.hosbv.com













	Ceperformer SCROLL COMPRESSOR		
1	MODEL: SZ185S4CC R 		
	THERMALLY PROTECTED SYSTEM SYSTEME DE PROTECTION THERMQUE 460 V 3 ~ 60 Hz 400 V 3 ~ 50 Hz		
	Abor V 3 C Max LR 175 A C Mav P.E.D. Ps = 25 bar C C C Marking Ts max = 63 °C C C C L.P. side Ts min = -35 °C 0082 0082 C		
	LUBRICANT: P.O.E. 160SZ		
	CAUTION Use of hydrocárbons is not approved of de ATTENTION L'utilisation d'hydrocarbures n'est pas autorisée par le fabricant REFRIGERANT:R407C R134a R404A R507		
	Panfoss Commercial Mape IN FRANCE		
	Manufactured under one or more of the following US or French parents and foreign counterparts thereto. US: 4840545, 4415317 French: 8906292, 8202323		
	Manufactured under one or more of analysis thereto. and foreign counterparts thereto. US: 4840545, 4415317 French: 8906292, 8202323		

Corols compressor Scrols compressor Model: SZ160T4CC
SYSTEM SYSTEM SYSTEM 460 V 3 ~ 60 Hz 400 V 3 ~ 50 Hz 29 A Max LR 150A P.E.D. Ps = 25 bar Marking Ts max = 63 °C LP. side Ts min = -35 °C LP. side Ts min = -35 °C
Termine 2000 LP. side Termine 2000 LUBRICANT: P.O.E. 1605Z LUBRICANT: P.O.E. 1605Z CAUTION Use of hydrocarbons is not approach training and the above of the approach of the a



Contraction of the second seco		
MODEL: SZ115S 		
THERMALLY PROTECTED SYSTEM 460 V 3 ~ 60 Hz 25 A Max	400 V 3 ~ 50 Hz LR 120 A	
P.E.D. Marking L.P. side Ps = 25 bar Ts max = 63 Ts min = -35 LUBRICANT:P.O.E.	°C 0038	
CAUTION Use of hydrou ATTENTION L'utilisation le fabricant		
Manufactured under one o and for US: 4840545. 4415317	Commercial SORS "more of the following US or French paper ign counterparts thereis French: 8906292, 8302121	





