

# Bitzer 6F-40.2Y-40P

## Specifications

Brand	Bitzer
Type	6F-40.2Y-40P
Refrigerant	Freon
kW at -5°C/+40°C	100,9
kW at -10°C/+40°C	83,1
kW at -20°C/+40°C	54,3
kW at -30°C/+40°C	33,0
kW at -40°C/+40°C	17,6
kW at -45°C/+40°C	11,7
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	42 liter
Suction accumulator	✓
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
m3 / h	151.6
Remarks	y.o.b. 2010
Sizes	1500x800x1120 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 6F-40.2Y-40P

Used Bitzer 6F-40.2Y-40P freeze-aggregate. Equipped with an AC&R oil separator, liquid receiver containing a volume of 42 liter, suction accumulator, liquid filter drier, pressure safety switches and multiple sight glasses. All mounted upon a steel base frame. The compressor has a headfan to exhaust excessive heat. Fan specs: Ziehl-Abegg functionable on both: 50 with 0,12 kW and 1410 RPM or 60 Hz with 0,19 kW and 1670 RPM. The diameter of the headfan is 300 mm.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.

\*If requested we are happy to arrange



Your partner for used commercial and  
industrial refrigeration equipment

---

your shipment.





