

Carrier 30 RA 200

Specifications

Brand	Carrier
Type	30 RA 200
Product type	Air Cooled Chiller
Capacity kW	202,0
Capacity Tons	57,4
Refrigerant	Freon
Refrigerant Type	R 407C
Pump	✓
Hydronic Module	✓
Sizes	3600x2260x1670 mm (LxWxH)
Compressor(s) type & model	4x Performer SZ185W4PC
Number of fans	4
Fan specifications	50 HZ - 0,75 KW - 710 rpm
Remarks	y.o.b: 2005
Stock	1



Description

Used Carrier 30 RA 200

Used Carrier 30 RA 200 air cooled chiller with 5 Performer SZ185W4PC scroll compressors. Evaporator PHE with a watervolume of 22 ltr, expansion vessel and a pump. Axial Flying Bird fans with rotating shroud 50 HZ - 0,75 KW - 710 rpm.

*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



99PS - 525 --- 172 -- EE - A

12Q503634
30RA-200-B0365-PEE--
30RA

2005/03/10

CE 0062

1 - (FR) NUMERO DE SÉRIE
(EN) SERIAL NUMBER
(DE) SERIENNUMMER

2 - MODÈLE - MODEL
MODELNUMMER

3 - VARIANTE - VARIANT
VARIANTE

4 - ANNÉE DE FABRICATION ET DATE D'ESSAI
YEAR OF MANUFACTURING AND TEST DATE
HERSTELLUNGSJAHR UND DATUM

5 - FLUIDE - MEDIUM R 407C
KALTEMITTEL

6 - GROUPE - GROUP
GRUPPE

7 - CHARGES CIRCUIT A
KALTEMITTELFÜLLUNG
KREISLAUF 1

21,0 kg

8 - CHARGES CIRCUIT B
KALTEMITTELFÜLLUNG
KREISLAUF 2

28,0 kg

9 - FLUIDE DE CONFINEMENT
CONFINEMENT MEDIUM
SICHERHEITSFÜLLUNGS-MEDIUM

23 --AZOTE--NITROGENE--

10 - PRESSION ADMISSIBLE MIN/MAX
ALLOWABLE PRESSURE MIN/MAX
ZULASSIGE MIN/MAX - DRUCKE

(PS) - 0,9 32,0 bar - 0,9 25,0 bar

11 - TEMPERATURES ADMISSIBLE MIN/MAX
ALLOWABLE TEMPERATURE MIN/MAX
ZULASSIGE MIN/MAX - TEMPERATUREN

(TS) - 20 72 °C - 20 62 °C

12 - PRESSION DE DÉCLenchement DES PRESSOSTATS
PRESSURE SWITCH SETTING
DRUCKSCHALTER-SOLLDRUCK

29,0 bar / bar

13 - PRESSION DE DÉCLenchement DES SOUPAPES
SAFETY RELIEF VALVE SETTING
SICHERHEITSENTLÜFT - SOLLDRUCK

/ bar 25,0 bar

14 - PRESSION D'ESSAI D'ÉTANCHÉITÉ DE L'UNITÉ
UNIT LEAK TEST PRESSURE
LECKTEST-DRUCK DES GERÄTS

15,0 bar

15 - TENSION
VOLTAGE
SPANNUNG

400 v 10 10 % 16 - PHASES 3

17 - FRÉQUENCE
FREQUENCY
FREQUENZ

~ 50 Hz 10 - MAXIMALE
MAXIMUM AMPS
MAXIMALSTROM

179,6 / A

18 - PUISSANCE ABSORBÉE MAX
MAX POWER INPUT
LEISTUNGSAUFNAHME

104,3 kW

20 - POIDS NET
NET WEIGHT
NETTOGEWICHT

2133 kg

24 - PRESSION DE DÉCLenchement DES DISQUES DE RUPTURE
RUPTURE DISKS SETTING
EINTEILDRUCK DER BERSTSCHEIBEN







/ bar / bar

MANUFACTURED IN FRANCE BY
CARRIER s.a.s - 01120 - MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK UNITED STATES OF AMERICA

Carrier





 SCROLL COMPRESSOR		
MODEL: SZ185W4PC		R
 SERIAL: RB11 5013796 		
ECHANTILLON CLIENT		
THERMALLY PROTECTED SYSTEM		SYSTEME DE PROTECTION THERMIQUE
460 V 3 ~ 60 Hz 34 A Max	400 V 3 ~ 50 Hz LR 155 A	
P.E.D. Marking L.P. side	Ps = 25 bar Ts max = 63 °C Ts min = -35 °C	 0038
LUBRICANT: P.O.E. 160SZ		
CAUTION Use of hydrocarbons is not approved by the manufacturer ATTENTION L'utilisation d'hydrocarbures n'est pas autorisée par le fabricant		
REFRIGERANT: R407C R134a R404A R507A		
	Danfoss Commercial Compressors	MADE IN FRANCE 2008 6001081P01A
Manufactured under one or more of the following US or French patents and foreign counterparts thereto. US: 4840545, 4415317 French: 8906292, 8202323		

