

Bitzer 4DC-7.2Y-40S Condensing unit

Specifications

Brand	Bitzer
Type	4DC-7.2Y-40S Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	21,0
kW at -5°C/+40°C	17,4
kW at -10°C/+40°C	14,3
kW at -20°C/+40°C	9,27
kW at -30°C/+40°C	5,51
kW at -40°C/+40°C	2,8
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	6 liter
Liquid line filter drier	✓
m3 / h	26,84 m3/h
Remarks	Y.o.b. 2009
Condensing Unit	✓
Sizes	1530x860x850 mm (LxWxH)
Stock	1




Description

Used Bitzer 4DC-7.2Y-40S Condensing unit

Used Bitzer 4DC-7.2Y-40S condensing unit. Complete with a Bitzer 4DC-7.2Y-40S semi-hermetic reciprocating compressor. Complete with liquid receiver 6 liter, liquid line filter drier and 2 air fans.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



Bitzer
ZER KÜHLMASCHINENBAU GMBH
Made in E.C.

Typ 4DC-7.2Y-40S
SNr. 1676600787

Spannung		Frequ.	Max. Betr. strom		Anlaufstrom		Fördervol.	Drehzahl
3Ph~	V Y 3Ph~	Hz	A (Δ)	A (Y)	A (Δ)	A (Y)	m³/h	min
0-240	380-420	50	27,5	15,9	142,8	82,4	26,9	1450
5-290	440-480	60	27,5	15,9	142,8	82,4	32,4	1750

65 ND/HD max. 19 / 28 bar



		LEGNAGO VERONA-Italy I-37045 S.p.A. www.frigomec.com			
Tipo		180/310VK00-RV-180X313			
Fabbricazione- Nr.		9106478			
Anno fabbricazione		2009			
GruppoFluidi		2	/	Escluso	/
Categoria		I	/	Volume V:L	6
Temperatura TS-°C		-10	100	-50	100
Press. max consentita PS-bar		33		24	
Pres di collaudo PT-bar		47.19			

