

Bitzer 6G.2Y (x2) & 4N.2Y (x1)

Specifications

Brand	Bitzer
Type	6G.2Y (x2) & 4N.2Y (x1)
Refrigerant	Freon
kW at -5°C/+40°C	206,1
kW at -10°C/+40°C	169,9
kW at -20°C/+40°C	111,5
kW at -30°C/+40°C	68,2
kW at -40°C/+40°C	37,0
kW at -45°C/+40°C	25,0
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure switches	✓
Oil separator	✓
Oil level system AC&R	✓
Solenoid Valve	✓
m3 / h	373,7
Remarks	SN: 1672714195 - Y.o.b. 2007
Remarks	SN: 1666105748 - Y.o.b. 2004
Remarks	SN: 1677105759 - Y.o.b. 2009



Package / Rack	✓
Sizes	2900x1650x2000 mm (LxWxH)
Stock	1

Description

Used Bitzer 6G.2Y (x2) & 4N.2Y (x1)

Used Bitzer semi-hermetic reciprocating rack on Freon. Complete with a Bitzer 4N.2Y that has a Rotor KF180L25 electric motor - 50 Hz - 7,5/11 kW - 980/1470 RPM, Bitzer 6G.2Y (x2) both with a Rotor electric motor - 50 Hz - 30 kW - 1465 RPM, oil separator, oil reservoir, oil level regulator and pressure and safety switches/gauges. The compressor rack has a total displacement of 373,7 m³/h.
*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.





