

Bitzer 4TCS-8.2Y-40S (x2) & 2CC-3.2Y-40S (x1)

Specifications

Brand	Bitzer				
Туре	4TCS-8.2Y-40S (x2) &				
	2CC-3.2Y-40S (x1)				
Refrigerant	Freon				
kW at -5ºC/+40ºC	66,0				
kW at -10ºC/+40ºC	54,2				
kW at -20ºC/+40ºC	35,2				
kW at -30ºC/+40ºC	21,1				
kW at -40ºC/+40ºC	11,0				
kW at -45ºC/+40ºC	7,1				
On steel base frame	✓				
Oil separator	1				
Oil level system AC&R	✓				
Sight Glass	✓				
Solenoid Valve	1				
m3 / h	98,8				
Remarks	Y.o.b. 2006				
Package / Rack	✓				
Sizes	1900x750x1100 mm				
	(LxWxH)				
Stock	1				



Description

Used Bitzer 4TCS-8.2Y-40S (x2) & 2CC-3.2Y-40S (x1)

Used Bitzer 4TCS-8.2Y-40P (x2) & 2CC-3.2Y-40S (x1) semi-hermetic reciprocating compressor rack on Freon. Complete with Alco OSH-411 oil separator with a volume of 3,6 liter and a electronic oil level regulator. The compressors together have a displacement of 98,8 m³/h. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your shipment.



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment

. <	Bitz				CS-8.2Y 0710079		
BITZER KÜHLMASCHINENBAU GMBH Made in E.C.							
Nennspannung V 3Ph~	Frequ. Hz	Betr.strom A (max.)	Anlaufstro	m A (YY)	Fördervol. m³/h	Drehzahl min ⁻¹	
380-420	50	17,0	49	81	41,3 49,9	1450 1750	
440-480	60	17,0	49	81	49,9	16	
IP 65 ND/HD	max. 19	9 / 28 bar				11	
37802805	a alla an	TRUSP SE					

Typ 4TCS-82Y-40P SNr 1670710072								
	Aade in							
Nennispannung V 3Ph~	Frequ. Hz	Betr.strom A (max.)	Anlaufstron A (Y)	n A (YY)	Fördervol. m³/h	Drehzahl min ⁻¹		
380-420	50	17,0	49	81	41,3	1450		
440-480	60	17,0	49	81	49,9	1750		
IP 65 ND/HD 1 37802805	P 65 ND/HD max. 19 / 28 bar							
		Stanks			19	and the second		







Your partner for used commercial and industrial refrigeration equipment



