

Bitzer 4G.2Y (x1) & 4G.2 (x1)

Specifications

Brand	Bitzer
Type	4G.2Y (x1) & 4G.2 (x1)
Refrigerant	Freon
kW at 0°C/+40°C	141,8
kW at -5°C/+40°C	117,5
kW at -10°C/+40°C	96,3
kW at -20°C/+40°C	62,4
kW at -30°C/+40°C	37,7
kW at -40°C/+40°C	20,2
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	204
Remarks	Y.o.b. 1996 - 4G.2 & Y.o.b. 2010 - 4G.2Y
Package / Rack	✓
Sizes	1200x1100x750 mm (LxWxH)
Stock	1



Description

Used Bitzer 4G.2Y (x1) & 4G.2 (x1)

Used Bitzer open-type reciprocating with 4G.2 & 4G.2Y compressors on Freon. Complete with a Rotor XC160L04 electric motor (x2) - 50 Hz - 15 kW - 1460 RPM, AC&R S-5692X oil separator, pressure and safety switches/gauges and sight glass. The compressors has a displacement of 204 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.









