

Bitzer 2CC-4.2Y-40S Condensing unit

Specifications

| | |
|--------------------------|--|
| Brand | Bitzer |
| Type | 2CC-4.2Y-40S Condensing unit |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 12,7 |
| kW at -5°C/+40°C | 10,5 |
| kW at -10°C/+40°C | 8,7 |
| kW at -20°C/+40°C | 5,6 |
| kW at -30°C/+40°C | 3,4 |
| kW at -40°C/+40°C | 1,8 |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid receiver ltr. | 13 |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| m3 / h | 50 Hz - 16,2 m³/h - 60 Hz - 19,6 m³/h |
| Remarks | Y.o.b. 2009 |
| Condensing Unit | ✓ |
| Sizes | 1100x820x950 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 2CC-4.2Y-40S Condensing unit

Used Bitzer LH84 condensing unit on Freon. Complete with a Bitzer 2CC-4.2Y-40S semi-hermetic reciprocating compressor, condenser with Ziehl-Abegg FB045-4EK.4I.V4P fans - 50 Hz - 0,48 kW - 1340 RPM - diameter 450 mm, Bitzer FS126 liquid receiver with a volume of 13 liters, liquid line filter driers and pressure and safety switches/gauges. The compressor has a displacement of 16,2 m³/h at 50 Hz and 19,6 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially.

*If requested we are happy to arrange



Your partner for used commercial and
industrial refrigeration equipment

your shipment.





