

Bitzer 4H

Specifications

Brand	Bitzer
Type	4H
Refrigerant	Freon
kW at 0°C/+40°C	60,0
kW at -5°C/+40°C	50,0
kW at -10°C/+40°C	41,2
kW at -20°C/+40°C	27,1
kW at -30°C/+40°C	16,7
kW at -40°C/+40°C	9,2
kW at -45°C/+40°C	6,4
Electromotor Specs	50 Hz - 11 kW - 1455 RPM
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Oil separator	✓
Sight Glass	✓
m3 / h	750 RPM - 38,0 m³/h / 1750 RPM - 88,8 m³/h
Remarks	Y.o.b. 1985
Condensing Unit	✓
Sizes	1250x750x800 mm (LxWxH)
Stock	1



Description

Used Bitzer 4H

Used Bitzer 4H open-type reciprocating compressor on Freon. Complete with a Rotor 1XF 160M04 500 electric motor - 50 Hz - 11 kW - 1455 RPM, oil separator, pressure and safety switch and sight glasses. The compressor has a displacement of 38,0 m³/h at 750 RPM and 88,8 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



