

DWM D4DL4-150X-AWM/D

Specifications

| | |
|------------------------------|-----------------------------|
| Brand | DWM |
| Type | D4DL4-150X-AWM/D |
| Refrigerant | Freon |
| kW at -20°C/+40°C | 27,1 |
| kW at -30°C/+40°C | 17,1 |
| kW at -40°C/+40°C | 9,9 |
| kW at -45°C/+40°C | 7,1 |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Condensing pressure switches | ✓ |
| Suction accumulator | ✓ |
| Oil separator | ✓ |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| Control panel | ✓ |
| m3 / h | 70,9 |
| Remarks | Y.o.b. 2001 |
| Sizes | 1750x770x1080 mm (LxWxH) |
| Stock | 1 |



Description

Used DWM D4DL4-150X-AWM/D

Used DWM D4DL4-150X-AWM/D semi-hermetic reciprocating compressor on Freon. Complete with a suction accumulator, oil separator, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 70,9 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.
*If requested we are happy to arrange your shipment.





