

Bitzer 6F-50.2 (x1) & 6G-40.2 Y (x2) & 6F-50.2Y-40P (x1)

Specifications

Brand	Bitzer
Type	6F-50.2 (x1) & 6G-40.2 Y (x2) & 6F-50.2Y-40P (x1)
Refrigerant	Freon
kW at 0°C/+40°C	448,6
kW at -5°C/+40°C	373,4
kW at -10°C/+40°C	307,8
kW at -20°C/+40°C	202,0
kW at -30°C/+40°C	123,8
kW at -40°C/+40°C	67,0
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	50 Hz - 556,8 m ³ /h
Package / Rack	✓
Sizes	5500x1000x1600 mm (LxWxH)
Stock	1



Description

Used Bitzer 6F-50.2 (x1) & 6G-40.2 Y (x2) & 6F-50.2Y-40P (x1)

Used semi-hermetic reciprocating Bitzer 6F-50.2 (x1) & 6G-40.2 Y (x2) & 6F-50.2Y-40P (x1) compressors rack on Freon. Complete with a 2 Henry Technologies AC&R S-5413 oil separator with volume of 20 liters, 2 Henry Technologies S-9108-CE oil reservoirs, pressure and safety switches/gauges and sight glasses. The compressors have a total displacement of 556,8 m³/h at 50 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

*Optionally we can also perform a new



paint job and arrange the logistics.







