

DWM DLSGP-40X-EWL & DKSJB-100/EWL/000 Condensing unit

Specifications

| Brand | DWM |
|--------------------------|-------------------------|
| Туре | DLSGP-40X-EWL & |
| | DKSJB-100/EWL/000 |
| | Condensing unit |
| Refrigerant | Freon |
| kW at -5ºC/+40ºC | 3,9* |
| kW at -10ºC/+40ºC | 3,2* |
| kW at -20ºC/+40ºC | 2,0*/7,7** |
| kW at -30ºC/+40ºC | 1,1*/4,5** |
| kW at -40ºC/+40ºC | 0,5*/2,1** |
| kW at -45ºC/+40ºC | 0,3*/1,2** |
| Pressure safety switches | 1 |
| Hp/Lp/Op | |
| Pressure gauges | 1 |
| Hp/Lp/Op | |
| Suction accumulator | 1 |
| Oil separator | 1 |
| Sight Glass | 1 |
| Control panel | 1 |
| m3 / h | DLGSP-40X-EWL - 22,5 |
| | m³/h & DWM |
| | DKSJB-100/EWL/000 - 6,3 |
| | m³/h |





| | **Capacity of the DWM DLSGP-40X-EWL | |
|--------------------|--|--|
| Btemoka rks | 1Capacity of the DWM | Description |
| | DKSJB-100/EWL/000 | Used DWM DLSGP-40X-EWL & DKSJB-100/EWL/000 Condensing unit |
| | | Used DWM DKSJB-100/EWL/000 wate |

Used DWM DKSJB-100/EWL/000 water cooled condensing unit. Complete with a DWM Copeland WP2 shell and tube condenser and pressure and safety switches/gauges. The compressor has a displacement of 6,3 m³/h.

Used DWM DLSGP-40X-EWL water cooled condensing unit on Freon. Complete with a DWM WR4 shell and tube condenser, oil separator, suction accumulator and pressure and safety switches/gauges. The compressor has a displacement of 22,5 m³/h.

Further the two condensing units comes with a shared control cabinet.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment











