

Mycom 200VMD 3.6

Specifications

Brand	Mycom
Type	200VMD 3.6
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	1357,8
kW at 0°C/+40°C	951,9
kW at -5°C/+40°C	786,8
kW at -10°C/+40°C	644,1
kW at -20°C/+40°C	417,5
kW at -30°C/+40°C	256,0
kW at -40°C/+40°C	144,9
kW at -45°C/+40°C	104,2
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
Remarks	*Liquid Subcooling 5°C. Suction Superheat 0°C. Rotation speed: 2950 RPM
Sizes	3800x1600x2300 mm (LxWxH)



Stock

1

Description

Used Mycom 200VMD 3.6

Used Mycom 200VMD 3.6 screw compressor on NH3 (ammonia) type R717. Complete with a Leroy-Somer PLS315M-T electric motor - 50/60 Hz - 200/230 kW - 2960/3565 RPM, Mycom HS 7530-200 oil separator with a volume of 155 liters, Mycom OC-15245 oil cooler, x2 Mycom OFC 50 oil filter, Grundfos UPS 65-180/2F water pump, Mycom M80P oil pump with a Electramo 1AR132M2-6 electro motor - 50 Hz - 5,5 kW - 960 RPM, oil cooler and a control cabinet.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.









