

Güntner GFH 102C/2*3 S (D)-F4 /3

Specifications

Brand	Güntner
Type	GFH 102C/2*3 S (D)-F4 /3
Product type	Drycooler
kW	250,6
Number of Fans	6
RPM of the Fans	430/310
Refrigerant	Glycol
Air Flow in m ³ /h	84.500
diameter fans Ø	1000 mm
Surface (m ²)	1190,5
Tube volume	221 dm ³
Sizes	7260x2400x1500 mm (LxWxH)
Stock	4



Description

Used Güntner GFH 102C/2*3 S (D)-F4 /3

Used Güntner GFH 102C/2*3S (D)-F4 /3 drycooler. Complete with 6 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,50/0,19 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 84.500 m³/h.

*Capacity based on the following:

Air inlet/outlet temperature:
25°C/33,9°C.

Medium Inlet/outlet temperature:
40°C/35°C.

Volume flow: 47,1 m³/h.

Medium: Glycol 34%.

Capacity of 625,1 kW based on the following:

Air inlet/outlet temperature:
25°C/47,3°C.

Medium Inlet/outlet temperature:
60°C/40°C.

Volume flow: 29,3 m³/h.

Medium: Glycol 34%.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.





