

Bitzer 6GE-34Y-40P

Specifications

| | |
|--------------------------|---|
| Brand | Bitzer |
| Type | 6GE-34Y-40P |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 105,2 |
| kW at -5°C/+40°C | 87,9 |
| kW at -10°C/+40°C | 72,9 |
| kW at -20°C/+40°C | 48,6 |
| kW at -30°C/+40°C | 30,6 |
| kW at -40°C/+40°C | 17,7 |
| kW at -45°C/+40°C | 12,7 |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| Control panel | ✓ |
| m ³ / h | 127 m ³ /h at 50 Hz & 153 m ³ /h at 60 Hz |
| Remarks | Y.o.b. 2016 |
| Condensing Unit | ✓ |
| Sizes | 5200x1800x1700 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 6GE-34Y-40P

Used condensing unit on Freon. Complete with a Bitzer 6GE-34Y-40P semi-hermetic reciprocating compressor, condenser with 6 EBM-Papst S3G500-SM06-H9 fans - 50/60 Hz - 0,50 kW - 1260 RPM - diameter 500 mm, liquid receiver, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 127 m³/h at 50 Hz & 153 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your shipment.





