

Sabroe SMC 108 S

Specifications

| | |
|--------------------|------------------------------------|
| Brand | Sabroe |
| Type | SMC 108 S |
| Refrigerant | NH 3 (ammonia) |
| kW at +10°C/+40°C | 571,1 |
| kW at 0°C/+40°C | 373,1 |
| kW at -5°C/+40°C | 294,4 |
| kW at -10°C/+40°C | 227,6 |
| Electromotor Specs | 50 Hz - 110 kW - 1466 RPM |
| Unloaded Start | ✓ |
| Capacity Control | ✓ |
| Oil separator | ✓ |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| Control panel | ✓ |
| m ³ / h | 295,4 m ³ /h at 975 RPM |
| Sizes | 2200x950x1500 mm (LxWxH) |
| Stock | 1 |



Description

Used Sabroe SMC 108 S

Used Sabroe SMC 108 S R717 (Ammonia) reciprocating compressor on a steel base frame. Complete with a Leroy Somer PLS280SC-T electric motor - 50 Hz - 110 kW - 1466 RPM, Sabroe oil separator with a volume of 62 liter and a Unisab 2 controller. The compressor has a displacement of 295,4 m³/h at 975 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.





