

Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Specifications

Brand	Bitzer
Type	4TCS-12.2Y-40P (x2) Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	64,2
kW at -5°C/+40°C	52,1
kW at -10°C/+40°C	41,8
kW at -20°C/+40°C	25,7
kW at -30°C/+40°C	14,5
Capacity Control	✓
Liquid receiver	✓
Liquid receiver ltr.	80
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
m ³ / h	82,6
Remarks	Y.o.b. 2009
Condensing Unit	✓
Sizes	4100x1300x2200 mm (LxWxH)
Stock	1



Description

Used Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Used Rivacold RV4C0278 condensing unit on Freon. Complete with a Bitzer x2 4TCS-12.2Y-40P semi-hermetic reciprocating compressors, condenser with 3 Ziehl-Abegg FE080-NDS.6K.V7 fans - 50 Hz - 0,37/0,20 kW - 440/340 RPM, Frigo Mec 324/1113VK01-FSR liquid receiver, OCS liquid receiver, Henry Technologies S-5690-CE oil separator, OCS-08 RLTU8 oil reservoir, 2 Danfoss frequency regulators and a control cabinet with a 2 Danfoss controllers and 2 Danfoss displays. The compressors have a total displacement of 82,6 m³/h at 50 Hz and 99,8 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only

the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.









