

Mycom FM160L-L

Specifications

Brand	Mycom
Type	FM160L-L
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	835,4
kW at 0°C/+40°C	579,6
kW at -5°C/+40°C	475,6
kW at -10°C/+40°C	385,6
kW at -20°C/+40°C	242,7
kW at -30°C/+40°C	140,7
Electromotor Specs	50/60 Hz - 132/152 kW - 2945/3538 RPM
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Sight Glass	✓
Control panel	✓
Remarks	Y.o.b. 2008
Weight in kg.	3300
Stock	1



Description

Used Mycom FM160L-L

Used Mycom / Mayekawa FM160L-L screw compressor skid on NH3 (Ammonia). Complete with a Leroy Somer PLS280MC-T electric motor - 50/60 Hz - 132/152 kW - 2945/3538 RPM, Mayekawa HS 6023 oil separator with a volume of 700 liter, Mayekawa OC-15245-V oil cooler, 2 Mayekawa OFC 50 oil filter, pressure and safety switches/gauges and a control cabinet with a Mycom MYPRO-CP3 controller.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.







