

Bitzer 6F-40.2Y (x2) & 6FF-80.2Y

Specifications

| | |
|--------------------------|--|
| Brand | Bitzer |
| Type | 6F-40.2Y (x2) & 6FF-80.2Y |
| Refrigerant | Freon |
| kW at -5°C/+40°C | 202,0 |
| kW at -10°C/+40°C | 166,2 |
| kW at -20°C/+40°C | 108,5 |
| kW at -30°C/+40°C | 65,9 |
| kW at -40°C/+40°C | 35,1 |
| kW at -45°C/+40°C | 23,4 |
| Capacity Control | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| Control panel | ✓ |
| m ³ / h | 50 Hz - 303,2 m ³ /h & 60 Hz - 362 m ³ /h |
| Package / Rack | ✓ |
| Sizes | 2550x2150x1800 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 6F-40.2Y (x2) & 6FF-80.2Y

Used Bitzer 6F-40.2Y (x2) & 6FF-80.2Y semi-hermetic reciprocating compressor Freon. Complete with pressure and safety switches/gauges, Vacon frequency regulator and a control cabinet with a Siemens OP7-DP controller. The compressors have a total displacement of 303,2 m³/h at 50 Hz & 362 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





