

Bitzer 4H.2 (x2)

Specifications

Brand	Bitzer
Type	4H.2 (x2)
Refrigerant	Freon
kW at +10°C/+40°C	119,1*
kW at 0°C/+40°C	99,2
kW at -5°C/+40°C	83,2
kW at -10°C/+40°C	68,7
kW at -20°C/+40°C	45,2
kW at -30°C/+40°C	27,8
kW at -40°C/+40°C	15,4
Electromotor Specs	11
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
Remarks	# // *Capacity based on +5°C/+40°C //
	Electromotor: 11 kW at 1455 RPM // Pulley EM: 180 mm Compr: 220 mm



	freon types
Packages / Rack	R404a - R22 or other
Sizes	2050x1500x2150 mm (LxWxH)
Stock	1

Description

Used Bitzer 4H.2 (x2)

Used Bitzer 4H.2 (x2) freon compressor rack, complete with unloaded start, safety pressure switches, pressure gauges, oil separator, liquid line filter drier, sight glass and control panel.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.







