

York / Frick 8 X F 880

Specifications

Brand	York / Frick
Type	8 X F 880
Refrigerant	Freon
kW at +10°C/+40°C	343
kW at 0°C/+40°C	231
kW at -10°C/+40°C	139
Stock	1



Description

Used York / Frick 8 X F 880

Used York / Frick 8 X F 880 single stage piston compressor *Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



R 22	COMPRESSEUR SIMPLE ETAGE MODELE 8 XF 88.1	88.1
------	--	------

Puissance frigorifique en kW
Puissance absorbée sur l'arbre en kW

Fluide frigorigène : R 22
Vitesse de rotation : 1450 tr/m
Volume engendré : 317.6 m

Température saturante d'aspiration en °C (To)

	18	16	14	12	10	8	6	4	2	0	-2	-4	-6	-8	-10
54	387	361	336	312	289	267	247	228	209	191	173	156	141	127	114
91	90	89	87	86	84	82	82	79	77	74	70	67	63	60	56
52	396	370	344	320	297	275	254	234	215	197	178	161	145	131	117
87	87	86	85	83	82	80	80	78	75	73	69	66	62	59	56
50	406	379	353	328	304	282	261	241	221	202	183	166	150	134	121
84	84	83	82	81	80	78	76	74	71	68	65	61	58	55	
48	415	388	362	336	312	289	268	247	227	208	188	170	154	138	124
80	80	80	79	79	77	76	74	72	70	67	64	61	57	54	
46	424	397	370	344	320	297	274	254	233	214	194	175	158	142	128
76	77	77	76	76	75	74	72	71	68	66	63	60	57	54	
44	433	405	379	353	328	304	281	260	240	219	199	180	163	146	131
72	73	73	73	73	72	72	70	69	67	64	61	59	56	53	
42	442	414	387	361	335	311	288	267	246	225	204	185	167	150	135
68	69	70	70	70	70	69	68	67	65	63	60	57	55	52	
40	451	423	395	369	343	319	295	273	252	231	210	190	172	154	139
63	65	66	67	67	67	67	67	66	65	63	61	59	56	54	51
38	460	431	404	377	351	326	302	280	258	237	215	195	176	159	143
59	61	62	63	64	64	64	64	64	63	62	60	57	55	53	50
36	468	439	412	385	358	333	309	287	265	243	220	200	181	163	146
54	56	58	60	61	61	61	61	61	61	60	58	56	54	52	49
34	477	448	420	392	366	341	316	293	271	249	226	205	185	167	150
49	52	54	56	57	58	58	58	58	58	57	56	54	52	50	48
32		456	427	400	373	348	323	300	277	255	232	210	190	171	154
47		50	52	53	55	55	55	56	56	55	54	53	51	49	47
30			435	407	381	355	330	307	284	261	237	215	195	176	158
45			48	50	51	51	52	53	53	53	52	51	49	48	46

Humidification
nécessaire
dans la zone
ombrée