

Bitzer 4DC-5.2Y-40S (x1) / 4CC-6.2Y-40S (x1)

Specifications

Brand	Bitzer					
Туре	4DC-5.2Y-40S (x1) /					
	4CC-6.2Y-40S (x1)					
Refrigerant	Freon					
kW at -5ºC/+40ºC	38,8					
kW at -10ºC/+40ºC	31,9					
kW at -20ºC/+40ºC	20,9					
kW at -30ºC/+40ºC	12,8					
kW at -40ºC/+40ºC	6,78					
kW at -45ºC/+40ºC	4,52					
On steel base frame	1					
Pressure safety switches 🗸						
Hp/Lp/Op						
Oil separator	1					
Package / Rack	1					
Sizes	1540x450x490 mm					
Stock	1					



Description

Used Bitzer 4DC-5.2Y-40S (x1) / 4CC-6.2Y-40S (x1)

Used Bitzer unit with 2 compressors, 4DC-5.2Y-40S and 4CC-6.2Y-40S, oil separators 7,1 ltr. Complete with pressure safety switches and control panel.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.

www.hosbv.com

info@hosbv.com




Your partner for used commercial and industrial refrigeration equipment





							d y			
B	Typ 4DC-5.2Y-40S SNr. 1667103229 Made in E.C. Image: Constraint of the second s									
1	Vennspann V & 3Ph~	ung V Y 3Ph~	Frequ. Hz	Max.Betr A (Δ)	A (Y)	Anlaufs A (Δ)	strom A (Y)	Fördervol. m ³ /h	Drehzahl min 1	
	220-240	380-420	50	23,4	13,5	107,7	62,2	26,9	1450	
	265-290	440-480	60	23,4	13,5	107,7	62,2	32,4	1750	
	P 65 ND/HD max. 19 / 28 bar									
				and Alicense Alicense	illine e Roberto		i.	2 4 A		

BITTER		CHINE		5			2Y-403 3240	S		
DITZER	BITZER KÜHLMASCHINENBAU GMBH Made in E.C.									
Nennspar V & 3Ph	nnung ∼VY3Ph~		Max.Betr A (Δ)	A (Y)	Anlaufs A (Δ)	A (Y)	Fördervol. m³/h	Drehzahl min		
220-240	380-420	50	27,5	15,9	141,8	82,4	32,5	1450		
265-290	440-480	60	27,5	15,9	141,8	82,4	39,2	1750		
P 65 ND/HD max. 19 / 28 bar										
		1	The second							







Your partner for used commercial and industrial refrigeration equipment

