

















Model	Capaciteiten in kW						Ventilatoren				
	R22		R134a		R404a		lucht m ³ /h ¹⁾	aantal	diameter mm	zonder 230/1/50	met 230/1/50
	DT1 -8°/8K	Dtm -7,5°/10K	DT1 -8°/8K	Dtm -7,5°/10K	DT1 -8°/8K	Dtm -7,5°/10K					























Lamellenafstand 3,2 mm

DKM 1*)	0,9	1,6	0,8	1,1	0,9	1,5	670	1	230		-
DKM 2	1,8	3,1	1,7	2,6	1,9	3,2	1340	2	230		-
DKM 3	2,6	4,9	2,7	4,7	2,9	5,0	2010	3	230		-
DKM 4	3,8	6,5	3,5		3,7		2680	4	230		-
DKM 5	4,6	8,3	4,6	7,6	4,9	8,3	3350	5	230		-























Lamellenafstand 3 mm

DKZ 61*)	1,90	4,3	2,1	3,9	2,2	4,6	1200	1	300		-
DKZ 62	3,98	8,6	4,2	8,1	3,7	9,3	2400	2	300		-
DKZ 63	6,46	13,0	6,4	12,3	6,5	14,1	3600	3	300		-
DKZ 64	8,18	18,2	8,3	14,1	7,6	18,8	4800	4	300		-
DKZ 65	10,70	22,6	10,1	21,2	10,7	23,0	6000	5	300		-
DKZ 66	12,37	27,6	12,9	25,0	11,6	28,3	7200	6	300		-
DKZ 81	5,05	11,8	4,9	8,7	5,3	12,1	2450	1	400		-
DKZ 82	10,17	23,9	10,2	18,7	10,7	24,6	4900	2	400		-
DKZ 83	15,09	34,0	15,5	33,5	14,5	37,2	7350	3	400		-
DKZ 84	20,41	47,9	20,7	38,9	21,5	49,9	9800	4	400		-
DKZ 85	26,22	58,3					12250	5	400		-

Lamellenafstand 4,5 mm

DNZ 61*)	1,50	3,1	1,6	3,1	1,8	3,9	1280	1	300		
DNZ 62	3,57	6,2	3,3	6,2	3,4	7,2	2560	2	300		
DNZ 63	5,49	10,1	5,1	8,1	5,7	10,9	3840	3	300		
DNZ 64	7,26	13,4	7,2	11,3	7,0	14,9	5120	4	300		
DNZ 65	9,23	17,2	7,6	15,8	9,3	17,6	6400	5	300		
DNZ 66	10,89	20,5	10,1	19,0	10,6	21,8	7680	6	300		
DNZ 81	4,22	8,1	4,4	7,8	4,6	9,7	2600	1	400		
DNZ 82	8,48	17,8	9,1	16,3	9,3	19,7	5200	2	400		
DNZ 83	13,54	26,7	12,9	26,4	13,3	29,0	7800	3	400		
DNZ 84	16,99	35,6	18,4	33,3	18,8	39,7	10400	4	400		
DNZ 85	23,62	45,8					13000	5	400		

Lamellenafstand 6 mm

DSZ 61*)	1,24	2,3	1,3	2,5	1,6	2,9	1370	1	300		
DSZ 62*)	3,16	5,6	2,7	5,1	3,1	5,8	2740	2	300		
DSZ 63	4,62	8,3	4,6	7,2	4,9	8,8	4110	3	300		
DSZ 64	6,41	11,3	6,1	10,1	6,4	12,1	5480	4	300		
DSZ 65	7,96	14,1	7,5	11,4	8,2	14,2	6850	5	300		
DSZ 66	9,66	17,0	8,2	15,6	9,6	17,6	8220	6	300		
DSZ 81	3,61	7,2	3,7	6,5	4,1	8,0	2750	1	400		
DSZ 82	7,25	14,4	7,5	13,3	8,2	16,1	5560	2	400		
DSZ 83	12,08	22,7	10,4	20,7	12,1	23,4	8340	3	400		
DSZ 84	14,61	28,9	15,2	17,1	16,5	32,5	11120	4	400		
DSZ 85	19,69	37,5	17,4	29,3	20,6	40,5	13750	5	400		

1) Gemeten bij een temperatuur van +20°C en een vrije doorlaat

* Geschikt voor ventiel zonder uitwendig drukvereffening

Voor de koelvermogens bij andere condities verwijzen wij u naar onze uitgebreide technische documentatie