



---

## Dry cooler

### Thermofin TCD 080.1-26-N(D5)

---

Capacity:	<b>603,0 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>226.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>35,0 °C</b>
Air outlet:	<b>33,7 °C</b>	Pressure drop:	<b>0,80 bar</b>
		Volume flow:	<b>113,3 m<sup>3</sup>/h</b>

---

Capacity:	<b>1370,2 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>226.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>44,9 °C</b>	Pressure drop:	<b>0,27 bar</b>
		Volume flow:	<b>64,3 m<sup>3</sup>/h</b>

---

Fans:	<b>12 Pieces 3~400V 50Hz</b>
Speed:	<b>880 min<sup>-1</sup></b>
Capacity:	<b>2,0 kW</b>

---

Surface:	<b>2674,0 m<sup>2</sup></b>	Tubes:	<b>Copper</b>
Tube volume:	<b>212,0 dm<sup>3</sup></b>	Fins:	<b>Aluminium</b>
Fin spacing:	<b>2,4 mm</b>	Passes:	<b>2</b>
		Distributions:	<b>178</b>