



---

## Dry cooler

### Güntner GFH 102C/2\*3 S (D)-F4/3

---

Capacity:	<b>250,6 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>84.500,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>35,0 °C</b>
Air outlet:	<b>33,9 °C</b>	Pressure drop:	<b>0,90 bar</b>
		Volume flow:	<b>47,1 m<sup>3</sup>/h</b>

---

Capacity:	<b>625,1 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>84.500,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>47,3 °C</b>	Pressure drop:	<b>0,36 bar</b>
		Volume flow:	<b>29,3 m<sup>3</sup>/h</b>

---

Fans:	<b>6 Pieces 3~400V 50Hz</b>
Speed:	<b>430 min<sup>-1</sup></b>
Capacity:	<b>0,50 kW</b>

---

Surface:	<b>1190,5 m<sup>2</sup></b>
Tube volume:	<b>221,0 dm<sup>3</sup></b>
Fin spacing:	<b>2,4 mm</b>