



---

## Dry cooler

Guntner GCHC RD 040.2/13-46-4234148M

---

Capacity:	<b>18,3 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>11.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>30,4 °C</b>
Air outlet:	<b>30,1 °C</b>	Pressure drop:	<b>0,80 bar</b>
		Volume flow:	<b>1,79 m<sup>3</sup>/h</b>

---

Capacity:	<b>43,8 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>11.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>37,5 °C</b>	Pressure drop:	<b>0,80 bar</b>
		Volume flow:	<b>1,86 m<sup>3</sup>/h</b>

---

Fans:	<b>3 Pieces 1~230V 50Hz</b>
Speed:	<b>1310 min<sup>-1</sup></b>
Capacity:	<b>0,19 kW</b>

---

Surface:	<b>64,5 m<sup>2</sup></b>	Tubes:	<b>Copper</b>
Fin spacing:	<b>2,4 mm</b>	Fins:	<b>Aluminium</b>
		Passes:	<b>6</b>
		Distributions:	<b>12</b>