



Water cooled
multi-scroll
chiller, standard
efficiency,
standard sound

EWVQ-L-SS



Scroll compressor

- › Dual refrigerant circuit (4 scroll compressors) with single evaporator
- › Heat pump version available
- › Compact design to allow easy indoor installation or retrofit operations
- › High efficiency and reliable scroll compressor
- › Stainless steel plate heat exchanger
- › High flexibility for a wide variety of applications
- › Allows sequencing control (up to 4 units) without any external device
- › Pump (low 100 kPa and high 200 kPa lift) available for evaporator and condenser

EWWQ-L-SS



EWWQ-L-SS

Heating only & Cooling only				EWWQ-L-SS															
				180	205	230	260	290	330	380	430	480	540	600	660	720			
Cooling capacity	Nom.			kW	187 (1)	215 (1)	244 (1)	273 (1)	303 (1)	345 (1)	387 (1)	430 (1)	476 (1)	549 (1)	611 (1)	663 (1)	721 (1)		
Heating capacity	Nom.			kW	234 (2)	269 (2)	305 (2)	339 (2)	377 (2)	430 (2)	486 (2)	537 (2)	601 (2)	692 (2)	773 (2)	843 (2)	917 (2)		
Power input	Cooling	Nom.		kW	41.7 (1)	47.3 (1)	53.1 (1)	60.2 (1)	67.1 (1)	77.1 (1)	87.0 (1)	97.9 (1)	110 (1)	124 (1)	140 (1)	154 (1)	167 (1)		
	Heating	Nom.		kW	50.5 (2)	57.5 (2)	65.0 (2)	73.6 (2)	82.0 (2)	94.4 (2)	107 (2)	118 (2)	133 (2)	150 (2)	171 (2)	188 (2)	204 (2)		
Capacity control	Method			Step															
	Minimum capacity			%	25.0	21.0	25.0	22.0	25.0	23.0	25.0	21.0	25.0	22.0	20.0	18.0	25.0		
EER					4.49	4.55	4.60	4.53	4.52	4.47	4.45	4.39	4.34	4.44	4.37	4.31	4.32		
ESEER					5.54		5.52	5.53	5.54	5.53	5.54	5.52	5.51	5.55	5.51		5.52		
COP					4.64 (2)	4.67 (2)	4.68 (2)	4.60 (2)		4.56 (2)	4.55 (2)	4.54 (2)	4.51 (2)	4.60 (2)	4.53 (2)	4.48 (2)	4.49 (2)		
IPLV					6.77	6.84	6.35	6.38	6.31	6.32	6.36	6.37	6.16	6.29	6.23	6.20	6.18		
Space heating	Average climate water outlet 35°C	General	ns (Seasonal space heating efficiency)	%	177	176	178	176	177										
				SCOP	4.08		4.14	4.24	4.23										
Dimensions	Unit	Height			mm	1,970							2,090	2,210					
		Width			mm								928						
		Depth			mm								2,801						
Weight	Unit			kg	877	1,062	1,285	1,347	1,439	1,498	1,559	1,673	1,722	1,842	1,926	2,105	2,229		
	Operation weight				kg	957	1,156	1,401	1,469	1,575	1,641	1,723	1,851	1,918	2,044	2,145	2,346	2,405	
Water heat exchanger - evaporator	Type			Plate heat exchanger															
	Water volume				l	35	41	53		65		76	92		115				
	Water flow rate	Nom.			l/s	9.0	10.3	11.7	13.0	14.5	16.5	18.5	20.6	22.8	26.3	29.3	31.8	34.6	
			Heating	Nom.		l/s	8.8	10.1	11.5	12.7	14.1	16.1	18.2	20.1	22.4	26.0	28.9	31.4	34.2
	Water pressure drop	Cooling	Nom.			kPa	28		23	28	25	32		33	40	51	50	59	69
Heating				Nom.		kPa	27	22	27	24	31		39	50	48	58	68		
Water heat exchanger - condenser	Type			Plate heat exchanger															
	Water volume				l	19	22	29		35		41	49		62				
	Water flow rate	Cooling	Nom.			l/s	5.5	6.3	7.2	8.1	9.0	10.2	11.4	12.7	14.0	14.5	18.0	17.9	21.3
				Heating	Nom.		l/s	11.3	13.0	14.8	16.5	18.3	20.9	23.5	25.9	28.9	33.4	37.2	40.5
	Water flow rate 2	Cooling	Nom.			l/s													
				Nom.			l/s	5.5	6.3	7.2	8.1	9.0	10.2	11.4	12.7	14.0	17.8	18.0	21.3
	Water pressure drop	Cooling	Nom.			kPa	72	73	61	49	50	51	55	46	57	43	67		68
				Heating	Nom.		kPa	76	77	64	52		53	59	48	60	70	72	73
Water pressure drop 2	Cooling	Nom.		kPa	72	73	61	49	50	51	55	46	57	66	67	68			
Compressor	Type			Scroll compressor															
	Quantity			4															
Sound power level	Cooling	Nom.		dB(A)	83	86	88	90	91		93	95		96					
Sound pressure level	Cooling	Nom.		dB(A)	65	68	70	72	74		73	76	77		78				
Operation range	Evaporator	Cooling	Min.-Max.	°CDB	-10~15														
	Condenser	Cooling	Min.-Max.	°CDB	25~55														
Refrigerant	Type / GWP			R-410A / 2,087.5															
	Circuits	Quantity			2														
Refrigerant charge	Per circuit			kg/TCO ₂ eq	10.0/ 20.9	11.0/ 23.0		12.0/ 25.1		15.0/313	16.0/334	17.0/ 35.5	19.0/397	20.0/ 41.8					
Piping connections	Evaporator water inlet/outlet (OD)			3"															
	Condenser water inlet/outlet (OD)			1" 1/2			2" 1/2					3"							
Unit	Starting current	Max			A	263	320	333	388	403	456	484	597	626	785	822	860	898	
			Running current	Cooling	Nom.	A	83	89	96	109	121	137	151	171	189	210	236	260	284
	Max				A	118	131	144	160	175	205	232	262	290	328	366	403	441	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400														

- (1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; entering condenser water temp. 30°C; leaving condenser water temp. 35°C; full load operation.
- (2) Heating capacity, unit power input and COP are based on the following conditions: evaporator 5/10°C; condenser 40/45°C, unit at full load operation.
- (3) Sound power (evap. 12/7°C, ambient 35°C full load operation) in accordance with ISO9614 and Eurovent 8/1 for Eurovent certified units. Certification refers only to the overall sound power, sound pressure is calculated from sound power level and used for info only, not considered bounding.
- (4) Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-437 10/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.