

Sabroe SAB 128 HF MK2 man VI

Specifications

Hersteller	Sabroe
Typ	SAB 128 HF MK2 man VI
Kältemittel	NH 3 (ammonia)
kW at +10°C/+40°C	610,3
kW at 0°C/+40°C	423,2
kW at -5°C/+40°C	347,9
kW at -10°C/+40°C	283,2
kW at -20°C/+40°C	214,8
kW at -30°C/+40°C	134,7
kW at -40°C/+40°C	77,8
E-Motor Specs	50 Hz - 49,5 kW - 2950 RPM
Leistungsregelung	✓
Auf einem Stahlrahmen	✓
Ölabscheider	✓
Schauglass	✓
Schaltschrank	✓
m3 / h	455,0
Größe	2350x1100x1530 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HF MK2 man VI

Gebrauchte Sabroe SAB 128 HF MK2 Kompressoreinheit auf NH3. Komplette mit 1 Sabroe SAB 128 HF MK2 Schraubenkompressor, Schorch KA7225M-AB014-151 - 50 Hz - 49,5 kW - 2950 U/min Elektromotor, Ölabscheider, Sabroe OWSG 1615 Ölkühler, Ölfilter, Pumpe und einem UNISAB S-Bedienpanel. Der Kompressor kann als Einzelkühlzweig mit einem anderen Elektromotor betrieben werden.





