

Profroid GQL ZF 40 Condensing unit

Specifications

Hersteller	Profroid
Typ	GQL ZF 40 Condensing unit
Kältemittel	Freon
kW at 0°C/+40°C	32,1
kW at -5°C/+40°C	26,5
kW at -10°C/+40°C	21,8
kW at -20°C/+40°C	14,3
kW at -30°C/+40°C	9,2
kW at -40°C/+40°C	5,6
Flüssigkeitssammler	✓
Flüssigkeitsfilter	✓
Schauglass	✓
m3 / h	35,3 m³/h at 50 Hz / 42,6 m³/h at 60 Hz
Bemerkungen	Y.o.b. 2008
Condensing Unit	✓
Größe	1230x650x1200 mm (LxWxH)
Stock	1



Description

Used Profroid GQL ZF 40 Condensing unit

Gebrauchte Profroid GQL ZF 40 Verflüssigungssatz auf Freon. Komplett mit 1 Copeland ZF41K5E-TFD-567 Scrollkompressor, Kondensator mit 2 EBM-Papst S6E450-AP02-06 Ventilatoren - 50/60 Hz - 0,17/0,23 kW - Durchmesser 450 mm und einem Flüssigkeitssammler. Die Kompressoren haben eine Gesamtverdrängung von 35,3 m³/h bei 50 Hz und 42,6 m³/h bei 60 Hz.





