

Aermec ANL030°A°°°°°

Specifications

Hersteller	Aermec
Typ	ANL030°A°°°°°
Product type	Air Cooled Chiller
Kälteleistung kW	7,5
Kälteleistung Tons	2,1
Kältemittel	Freon
Kältemittel Typ	R410A
Pump	✓
Gewicht in kg.	103
Größe	1150x400x1020 mm (LxWxH)
Compressor(s) type & model	x1 Copeland ZP32K3ETFD 400/3
Display	Aermec display
Number of fans	1
Fan specifications	50/60 Hz - 0,14/0,19 kW - 870/930 RPM
Bemerkungen	Y.o.b. 2013
Stock	1



Description

Used Aermec ANL030°A°°°°°

Gebrauchter luftgekühlter Aermec ANL030°A°°°°° auf Freon R410A. Komplet mit 1 Copeland ZP32K3ETFD 400/3 Scroll-Kompressor, Kondensator mit 1 Ebm-papst A6E450-AQ15-12 Lüfter - 50/60 Hz - 0,14/0,19 kW - 870/930 U/min, Koaxialverdampfer, Wilo TOP-RL25/8,5AE Wasserpumpe, Zilmet Ausdehnungsgefäß und einem Schaltschrank mit Aermec-Display.



30-35 °C		40-45 °C		47-55 °C		12-7 °C	
7/6°C (DB/WB)		7/6°C (DB/WB)		7/6°C (DB/WB)		35 °C	
PH[kW]	0.00	PH[kW]	0.00	PH[kW]	0.00	PC[kW]	7.50
PE[kW]	0.00	PE[kW]	0.00	PE[kW]	0.00	PE[kW]	2.61
COP[W/W]	0.0	COP[W/W]	0.0	COP[W/W]	0.0	EER[W/W]	2.87
In[A]	0.00	In[A]	0.00	In[A]	0.00	In[A]	5.70
RES EL / EL HEATER [kW]	0.00	Is[A]	37	Imax[A]	7.70		
RES EL / EL HEIZUNG [A]	0.00	R410A [Kg]	1.56				
TS (HP/LP) [°C]	Min -10 / -16	PS (HP/LP) [bar]	42 / 25				
	Max 120 / 52	Versione SW:	4.4.2				

ANL030°A°°°°°-1303005163960002







