

# Bitzer 4CC-6.2Y-40S Water-cooled condensing unit

## Specifications

Hersteller	Bitzer
Typ	4CC-6.2Y-40S Water-cooled condensing unit
Kältemittel	Freon
kW at -5°C/+40°C	21,1
kW at -10°C/+40°C	17,4
kW at -20°C/+40°C	11,4
kW at -30°C/+40°C	7,0
kW at -40°C/+40°C	3,8
kW at -45°C/+40°C	2,5
Druckschalter	✓
Flüssigkeitsfilter	✓
Schauglass	✓
m <sup>3</sup> / h	32,5
Bemerkungen	Y.o.b. 2004
Gewicht in kg.	118
Condensing Unit	✓
Größe	1000x400x700 mm (LxWxH)
Stock	4



## Description

### Used Bitzer 4CC-6.2Y-40S Water-cooled condensing unit

Gebrauchte wassergekühlte Bitzer-Verflüssigungsanlage mit Freon-Betrieb. Komplett mit einem halbhermetischen Kolbenkompressor Bitzer 4CC-6.2Y-40S, einem Rohrbündelverflüssiger Bitzer K203H, Druck- und Sicherheitsschaltern sowie Schauglas. Der Kompressor hat eine Förderleistung von 32,5 m<sup>3</sup>/h bei 50 Hz und 39,2 m<sup>3</sup>/h bei 60 Hz.



