

Mycom FM160L-L

Specifications

Hersteller	Mycom
Typ	FM160L-L
Kältemittel	NH 3 (ammonia)
kW at +10°C/+40°C	835,4
kW at 0°C/+40°C	579,6
kW at -5°C/+40°C	475,6
kW at -10°C/+40°C	385,6
kW at -20°C/+40°C	242,7
kW at -30°C/+40°C	140,7
E-Motor Specs	50/60 Hz - 132/152 kW - 2945/3538 RPM
Anlaufentlastung	✓
Leistungsregelung	✓
Auf einem Stahlramen	✓
Druckschalter	✓
Druckmanometer	✓
Ölabscheider	✓
Schauglass	✓
Schaltschrank	✓
Bemerkungen	Y.o.b. 2008
Gewicht in kg.	3300
Stock	1



Description

Used Mycom FM160L-L

Gebrauchter Mycom/Mayekawa FM160L-L Schraubenkompressor auf Ammoniak-Basis. Komplett mit einem Leroy Somer PLS280MC-T Elektromotor (50/60 Hz, 132/152 kW, 2945/3538 U/min), einem Mayekawa HS 6023 Ölabscheider (700 Liter), einem Mayekawa OC-15245-V Ölkühler, zwei Mayekawa OFC 50 Ölfiltern, Druck- und Sicherheitsschaltern/Manometern sowie einem Schaltschrank mit Mycom MYPRO-CP3 Steuerung.







