

Bitzer 4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1)

Specifications

Hersteller	Bitzer
Typ	4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1)
Kältemittel	Freon
kW at 0°C/+40°C	62,0
kW at -5°C/+40°C	51,5
kW at -10°C/+40°C	42,3
kW at -20°C/+40°C	27,6
kW at -30°C/+40°C	16,6
kW at -40°C/+40°C	8,7
kW at -45°C/+40°C	5,7
Leistungsregelung	✓
Auf einem Stahlrahmen	✓
Druckschalter	✓
Druckmanometer	✓
Ölabscheider	✓
Ölniveauregelung AC&R	✓
Schauglass	✓
m ³ / h	80
Package / Rack	✓
Größe	3150x1300x1020 mm (LxWxH)
Stock	1



Description

Used Bitzer 4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1)

Gebrauchte Bitzer 4FC-5.2 Y (x3), 2CC-4.2 Y (x1) und 2FC-3.2 Y (x1) halbhermetische Kolbenkompressoren mit Freon-Befüllung. Komplett ausgestattet mit Henry Technologies S-9109-CE, Ölabscheider, Druck- und Sicherheitsschaltern/Manometern sowie einem Ölstandsanzeigesystem AC&R. Die Kompressoren haben eine Förderleistung von 80,0 m³/h bei 50 Hz und 96,0 m³/h bei 60 Hz.





