

Sabroe SAB 128 HF mk2 (x2) package

Specifications

Hersteller	Sabroe
Typ	SAB 128 HF mk2 (x2) package
Kältemittel	NH 3 / Freon
kW at -10°C/+40°C	176.4
kW at -20°C/+40°C	283
E-Motor Specs	37 kW at 2935 RPM
Auf einem Stahlrahmen	✓
Flüssigkeitssammler	✓
Ölabscheider	✓
Bemerkungen	Capacity based on -40°C/-10°C / -30°C/-5°C // Electromotor: 37 kW at 2935 RPM // Booster Compressors // Can also be used as Freon set / 212,2 at -40°C/-10°C / 319 at -30°C/-5°C
Package / Rack	✓
Stock	1



Description

Used Sabroe SAB 128 HF mk2 (x2) package

Gebrauchte Sabroe SAB 128HF Schraubenkompressorkufe. Für alle anderen Spezifikationen siehe das Bild des Herstellermodells oder die angehängte PDF-Datei (falls verfügbar).
* Warum für HOSBV wählen? Wir waren nicht nur der größte Spezialist für gebrauchte Kältetechnik in Europa, sondern liefern auch alle Geräte einschließlich umfassender Tests, Garantien und industrieller Reinigung. * Optional können wir auch einen neuen Anstrich durchführen und die Logistik organisieren.




SAB 128 screw compressor block with balanced overflow valve type POV

Cooling capacities * kW at 2960 rpm									
Model	R717		R22		R404A		With economiser		
	High stage	Booster	High stage	High stage	High stage	R717	R22	R404A	
SAB 128 HM	187.9	58.9	178.4	240.5	183.9	245.4	50.3	64.7	73.5
SAB 128 HF	294.9	92.5	280.0	379.4	288.6	385.2	78.9	101.0	113.9

* 5 °K liquid sub-cooling / 5 °K suction superheat for R717 / 15 °C suction superheat for R404A and R22

Technical data						
Model	Swept volume ⁽¹⁾		Length ⁽²⁾	Dimensions ⁽³⁾		Weight ⁽⁴⁾
	2950 rpm	3550 rpm		Width	Height	
SAB 128 HM	303	364	2200	1420	1405	1150
SAB 128 HF	454	547	2200	1420	1405	1150

(1) Drive motor speed – (2) With refrigerant-cooled oil cooler – (3) Excluding electric motor – (4) Free field – one metre distance

All data are subject to change without notice

SAB 0009