

Roller HVS 407

Specifications

Hersteller	Roller
Typ	HVS 407
Kälteleistung kW	4.12
Kältemittel	Freon
Anzahl der Ventilatoren	1
Ventilator Durchmesser in mm	7
Abtauung	Electric
Luftdurchsatz in m ³ /h	4000
Bemerkungen	YOB 2003
Remarks	31 m ²
Volume	5.9 dm ³
Gewicht	43 kg
Stock	1



Description

Used Roller HVS 407

Used but in good condition a Roller HVS 407 evaporator with 4.12kW and 4000 m³/h, 5.9 dm³ and 31m². *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.



400-414			Lamellenabstand 4,5 mm			Fin spacing 4,5 mm			Separación de aletas 4,5 mm		
Typ Modelo	Leistung Capacity Potencia		Oberfläche Surface Superficie	Lufteinmenge Caudal de air	Wurfweite Air throw Proyección de air		Schalldruckpegel Sound power level Potencia sonora	Schalldruckpegel Sound level Presión sonora	Anschlüsse Connections Conexiones		
	LT = -8 °C	LT = -25 °C							Eintritt Inlet Entrada	Austritt Outlet Salida	
	DT = 8 K	DT = 7 K					dB(A)	dB(A)**	Ø mm	Ø mm	
HVS/HVST	kW	kW	m²	m³/h	m	m	dB(A)	dB(A)**	Ø mm	Ø mm	
400	0,60	0,35	5,3	1180	5	14	62	49	12	12	
401	0,89	0,56	7,9	1130	5	14	62	49	12	12	
402	1,25	0,86	10,3	1590	6	12	64	51	12	15	
403	1,63	1,19	13,8	1530	6	12	64	51	12	15	
404	2,04	1,66	16,2	2160	13	-	74	61	12	15	
405	2,63	2,14	21,5	2660	13	-	74	61	12	18	
406	3,14	2,56	31,2	2660	13	-	74	60	12*	18	
407	4,14	3,35	31,0	4000	14	29	73	59	12*	22	
408	5,21	4,23	36,7	3940	14	29	73	59	12*	22	
409	6,47	5,26	50,0	4630	15	31	77	63	12*	22	
410	7,69	6,26	60,7	5530	16	32	78	64	12*	28	
411	9,06	7,37	71,4	6350	17	34	81	67	12*	28	
412	12,60	10,20	91,8	9160	18	36	80	65	15*	35	
413	15,70	12,80	128,5	11100	19	40	81	66	15*	42	
414	19,00	15,40	157,0	12900	20	45	84	69	15*	42	

Mehrfachspritzung mit Schraudenarm am Austritt

Multipoint injection with Schrader valve at the outlet

Min. Schalldruckpegel in 1 m Abstand (1 m fern) schallfeldförmige Schallausbreitung)

Mean sound pressure level at a distance of 1 m in semi-reverberant field

** Precision sonora en 1 m de distancia en campo semireverberante

** Mean sound pressure level at a distance of 1 m in semi-reverberant field

* Mehrfachspritzung mit Schrägventil am Austritt
* Multiple injection with Schrägventil at the outlet
* Inyección múltiple a la salida de la válvula

** Mittel Schalldruckpegel in 1 m Abstand im Freifeld (halbkugelförmige Schallabstrahlung)
** Mean sound pressure level at a distance of 1 m in semi-reverberant field
** Presión sonora media a 1 m de distancia en campo semi-reverberante