

# Güntner GVH 065.1A/2

## Specifications

Brand	Güntner
Type	GVH 065.1A/2
Product type	Air Cooled Condenser
kW	52,1
Number of Fans	2
RPM of the Fans	650/490
Refrigerant	Freon
Air Flow in m <sup>3</sup> /h	12.440
diameter fans Ø	650 mm
Surface (m <sup>2</sup> )	136
Tube volume	30 dm <sup>3</sup>
Sizes	2310x1140x1480 mm (LxWxH)
Weight	184 kg
Stock	1



## Description

### Used Güntner GVH 065.1A/2

Used Güntner GVH 065.1A/2 air cooled condensor. Complete with 2 Ziehl-Abegg fans 50 Hz - 0,20/0,09 kW - 650/490 RPM - diameter 650 mm. Mentioned capacity at delta is 52,1 kW and capacity at star is 42,0 kW.

\*All components of this used condensor will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.





		$\dot{Q}_{ev}$	$\dot{V}_l$		aufgenommene el. Leistung			Energieeffizienzklasse Energy efficiency class	Schalldruck- pegel		Strang- Anzahl	Gewicht	Rohr- volumen	Fläche			
Typ	Nennleistung	Luftvolumenstrom		ei Leistung			Sound pressure level										
		Nominal capacity		consumed power													
		Type	R404A $\Delta t = 15\text{ K}$		$P_{e, total}$												
	$\Delta$	Y	$\Delta$	Y	$\Delta$	Y	$\Delta / Y$	$\Delta$	Y								
	kW	kW	m³/h	m³/h	kW	kW		dB(A)10m			kg	l	m²				
045.1A/1 ... W	11,7	—	2570	—	0,12	—	B	31	—	4	61	8	40				
045.1C/1 ... W	13,6	—	2890	—	0,12	—	A	31	—	6	72	10	54				
045.1A/2 ... W	23,8	—	5210	—	0,24	—	B	34	—	9	108	15	83				
045.1C/2 ... W	27,8	—	5830	—	0,23	—	A	34	—	9	133	19	111				
045.1A/3 ... W	35,8	—	7850	—	0,35	—	B	35	—	13	156	23	126				
045.1C/3 ... W	41,4	—	8770	—	0,35	—	A	35	—	18	192	30	167				
050.1A/1 ... D+S	16,0	13,4	3650	2920	0,13	0,09	A / A	31	27	6	82	11	50				
050.1C/1 ... D+S	19,2	16,1	4080	3310	0,13	0,08	A / A	31	27	6	96	16	73				
050.1A/2 ... D+S	32,6	27,3	7390	5920	0,26	0,17	A / A	34	30	12	152	22	104				
050.1C/2 ... D+S	38,6	32,5	8190	6640	0,26	0,17	A / A	33	29	12	179	31	150				
050.1A/3 ... D+S	49,6	41,5	11120	8910	0,4	0,26	A / A	35	31	15	221	32	157				
050.1B/3 ... D+S	54,6	45,9	11850	9560	0,39	0,26	A / A	35	31	15	241	40	191				
050.1C/3 ... D+S	58,0	48,8	12300	9980	0,38	0,25	A / A	35	31	20	261	47	226				
050.1B/4 ... D+S	72,9	61,3	15810	12770	0,52	0,34	A / A	36	32	20	321	53	256				
065.1A/1 ... D+S	25,2	20,2	6150	4850	0,36	0,23	B / B	40	33	10	99	16	66				
065.1B/1 ... D+S	28,4	23,1	6640	5100	0,35	0,23	B / B	40	33	10	112	19	81				
065.1C/1 ... D+S	30,9	25,2	6980	5420	0,34	0,22	B / A	40	33	10	123	22	96				
065.1A/2 ... D+S	52,1	42,0	12440	9840	0,72	0,46	B / B	43	36	16	184	30	156				
065.1B/2 ... D+S	57,9	46,7	13390	10290	0,7	0,45	B / B	42	35	20	207	36	166				
065.1C/2 ... D+S	62,5	51,0	14040	10910	0,68	0,45	B / A	42	35	20	230	43	196				
065.1A/3 ... D+S	79,2	63,9	18740	14220	1,07	0,69	B / B	44	37	20	268	46	206				
065.1B/3 ... D+S	87,5	71,0	20130	15490	1,05	0,68	B / B	44	37	27	302	56	251				
065.1C/3 ... D+S	94,5	77,1	21090	16390	1,02	0,67	B / A	44	37	27	345	66	296				
065.1B/4 ... D+S	116,8	94,3	26870	20680	1,4	0,9	B / B	45	38	41	473	73	336				