

Thermocold CWC Prozone 1170 ZH

Specifications

Brand	Thermocold
Type	CWC Prozone 1170 ZH
Product type	Water Cooled Chiller
Capacity kW	168,1
Refrigerant	Freon
Refrigerant Type	R-410A
Weight in kg.	671 Kg
Sizes	1460x700x1710 (LxWxH)
Compressor(s) type & model	Danfoss SH240A4ABE
Display	Carel pGD-i
Remarks	Y.O.B. 2015
Stock	1



Description

Used Thermocold CWC Prozone 1170 ZH

Used Thermocold CWC Prozone 1170 ZH watercooled chiller. Complete with 2 Danfoss SH240A4ABE scroll compressors, 2 Plate heat exchangers and a liquid line filter drier. This chiller contains a Carel pGD-i user interface. *All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. Also, we can arrange your shipment.



		Thermocold Costruzioni S.r.l. Via del Ciclamini, 25 70026 Z.I. Modugno (Bari) Italy Tel. 080/5312623 - 5312562 Fax. 080/5312560 Web site: www.thermocold.it E-mail: info@thermocold.it
		
Modello - Type	CWC PROZONE 1170 ZH	
Matricola unità - Serial number	GZ-1480-G0	
Anno costruzione - Manufact. year	2015	
Peso in funzionamento (Kg) Operation weight (Kg)	788	
Contiene gas fluorurati ad effetto serra disciplinati dal protocollo di Kyoto. Contains fluorinated greenhouse gases covered by the Kyoto Protocol.		
Gas refrigerante - Refrigerant	R410A	
Carica refrigerante (Kg) Refrigerant charge (Kg)	14	
Tipo di olio - Oil type	P.O.E. 160 SZ	
Alimentazione elettrica - Power supply		
Tensione - Voltage V / Ph / Hz	400/3+n/50	
F.L.I. (kW)	64.6	
F.L.A. (A)	113	
Massima pressione ammissibile (PS) - Max allowable pressure (PS)		
Circuito gas - Gas circuit	LP 24.5 bar - HP 45 bar	
Circuito acqua - Water circuit	10 bar	
Massima temperatura di stoccaggio e trasporto: 55°C Maximum transport and storage temperature: 55°C		
 GZ-1480-G0		





