

Bitzer 4G-30.2Y-40P (x5)

Specifications

| Brand | Bitzer |
|--------------------------|-------------------|
| Туре | 4G-30.2Y-40P (x5) |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 342,8 |
| kW at -5ºC/+40ºC | 285,1 |
| kW at -10ºC/+40ºC | 234,9 |
| kW at -20ºC/+40ºC | 153,5 |
| kW at -30ºC/+40ºC | 93,1 |
| kW at -40°C/+40°C | 49,2 |
| Capacity Control | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Oil separator | ✓ |
| Oil level system AC&R | ✓ |
| Solenoid Valve | ✓ |
| m3 / h | 422,5 |
| Package / Rack | ✓ |
| Sizes | 3050x1450x1660 mm |
| | (LxWxH) |
| Stock | 1 |
| | |



Description

Used Bitzer 4G-30.2Y-40P (x5)

Used Bitzer 6G-40.2Y (x5) Semihermetic reciprocating compressor. Complete with oil level system AC&R, oil separator and pressure and safety switches/gauges.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if they passed our extensive test. If requested we are happy to arrange your shipment.



















Your partner for used commercial and industrial refrigeration equipment







HOS BV www.hosbv.com info@hosbv.com (+31) (0)23-5404237