

Bitzer 4T.2 Condensing unit

Specifications

Brand	Bitzer
Туре	4T.2 Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	33,1
kW at -5°C/+40°C	27,6
kW at -10ºC/+40ºC	22,8
kW at -20°C/+40°C	15,1
kW at -30°C/+40°C	9,4
kW at -40ºC/+40ºC	5,2
kW at -45°C/+40°C	3,7
Electromotor Specs	50/60 Hz - 7,5/9,0 kW -
	1445/1735 RPM
On steel base frame	1445/1735 RPM
On steel base frame Liquid receiver	
	/
Liquid receiver	/ /
Liquid receiver Liquid receiver ltr.	//19
Liquid receiver Liquid receiver ltr. Liquid line filter drier	/19/
Liquid receiver Liquid receiver ltr. Liquid line filter drier Sight Glass	/19/
Liquid receiver Liquid receiver ltr. Liquid line filter drier Sight Glass m3 / h	/19//47,4
Liquid receiver Liquid receiver ltr. Liquid line filter drier Sight Glass m3 / h Condensing Unit	✓ ✓ 19 ✓ ✓ 47,4 ✓
Liquid receiver Liquid receiver ltr. Liquid line filter drier Sight Glass m3 / h Condensing Unit	✓ 19 ✓ 47,4 ✓ 2150x750x1250 mm



Description

Used Bitzer 4T.2 Condensing unit

Used Bitzer 4T.2 condensing unit on Freon. Complete with 1 Bitzer 4T.2 open-type reciprocating compressors, condenser with 2 fans and a diameter of 400 mm, AEG AM 132 AMR elektromotor: 50 Hz - 7,5 kW - 1445 RPM, liquid receiver with a volume of 19 liters, liquid line filter and a control box.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



Your partner for used commercial and industrial refrigeration equipment



























Your partner for used commercial and industrial refrigeration equipment

