

Carrier 30 RH 060

Specifications

Brand	Carrier
Type	30 RH 060
Product type	Heat pump
Capacity kW	54,0* / 57,0**
Capacity Tons	15,4* / 16,2**
Refrigerant	Freon
Refrigerant Type	R407C
Liquid buffer tank	✓
Pump	✓
Hydronic Module	✓
Weight in kg.	727
Sizes	2100x1070x1330 mm (LxWxH)
Compressor(s) type & model	1 Performer SZ120S4VC & 1 Performer SZ161T4VC
Display	Carrier Pro-Dialog Plus
Number of fans	1
Fan specifications	400 V - 50 Hz - 0,9/0,45/0,12 kW - 700/600/300 RPM
Remarks	Y.o.b. 2004
Remarks	*Cooling capacity
Remarks	**Heating capacity
Stock	1



Description

Used Carrier 30 RH 060

Used Carrier 30 RH 060 heat pump on R407C. Complete with 1 Performer SZ120S4VC & 1 Performer SZ161T4VC scroll compressors, condenser with 1 fan - 400 V - 50 Hz - 0,9/0,45/0,12 kW - 700/600/300 RPM, plate heat exchanger with a volume of 5,9 dm³, liquid tank with a volume of 14 liter, 2 Salmson JRL204-13/2,2 water pumps, expansion vessel and a Carrier Pro-Dialog Plus.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



99PS - 525 --- 172 -- EE - A

1 - (FR) NUMERO DE SÉRIE
(EN) SERIAL NUMBER
(DE) SERIENNUMMER
12S408239

2 - MODÈLE - MODEL
MODELNUMMER
30RH-060-B0053-PEE--

3 - VARIANTE - VARIANT
VARIANTE
30RH

4 - ANNÉE DE FABRICATION ET DATE D'ESSAI
YEAR OF MANUFACTURING AND TEST DATE
HERSTELLUNGSAHR UND DATUM
2004/05/26

5 - FLUIDE - MEDIUM
KALTEMITTEL
R 407C

6 - GROUPE - GROUP
GRUPPE
2

7 - CHARGES CIRCUIT A
KALTEMITTELFÜLLUNG
KREISLAUF 1
15,1 kg

8 - CHARGES CIRCUIT B
KALTEMITTELFÜLLUNG
KREISLAUF 2
/ kg

9 - FLUIDE DE CONFINEMENT
CONFINEMENT MEDIUM
SICHERHEITTSFÜLLUNGS-MEDIUM
23 --AZOTE--NITROGENE--

10 - PRESSION ADMISSIBLE MIN/MAX
ALLOWABLE PRESSURE MIN/MAX
ZULASSIGE MIN/MAX - DRUCKE
(PS) 0,9 32,0 bar - 0,9 25,0 bar

11 - TEMPERATURES ADMISSIBLE MIN/MAX
ALLOWABLE TEMPERATURE MIN/MAX
ZULASSIGE MIN/MAX - TEMPERATUREN
(TS) - 20 72 °C - 20 62 °C

12 - PRESSION DE DÉCLenchement DES PRESSOSTATS
PRESSURE SWITCH SETTING
DRUCKSCHALTER-SOLLDRUCK
29,0 bar / bar

13 - PRESSION DE DÉCLenchement DES SOUPAPES
SAFETY RELIEF VALVE SETTING
SICHERHEITSVENTIL - SOLLDRUCK
32,0 bar 25,0 bar

14 - PRESSION D'ESSAI D'ÉTANCHÉITÉ DE L'UNITÉ
UNIT LEAK TEST PRESSURE
LECKTEST-DRUCK DES GERÄTS
15,0 bar

15 - TENSION
VOLTAGE
400 v

16 - PHASES
PHASEN
3

17 - FREQUENCE
FREQUENCY
50 Hz

18 - I MAXIMALE
MAXIMUM AMPS
MAXIMALSTROM
54,4 / A

19 - PUISSANCE ABSORBÉE MAX
MAX POWER INPUT
LEISTUNGS-AUFNAHME
31,7 / kW

20 - POIDS NET
NET WEIGHT
727 kg

24 - PRESSION DE DÉCLenchement DES DISQUES DE RUPTURE
RUPTURE DISK SETTING
EINSTELLDRUCK DER BERSTSCHEIBEN
/ bar / bar

MANUFACTURED IN FRANCE BY
CARRIER S.A.S - 01120 - MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK UNITED STATES OF AMERICA

Carrier









