

### Bitzer 4N-12.2Y (x3)

### **Specifications**

Brand	Bitzer
Туре	4N-12.2Y (x3)
Refrigerant	Freon
kW at -5ºC/+40ºC	114,0
kW at -10ºC/+40ºC	93,2
kW at -20ºC/+40ºC	61,2
kW at -30ºC/+40ºC	36,9
kW at -40ºC/+40ºC	20,1
On steel base frame	1
Pressure safety switches	1
Hp/Lp/Op	
Pressure gauges	1
Hp/Lp/Op	
m3 / h	168,3
Power	50hz/60hz 3Ph
Remarks	Y.o.b. 2002
Package / Rack	1
Sizes	1700x800x1750 mm
	(LxWxH)
Stock	1



#### **Description**

#### Used Bitzer 4N-12.2Y (x3)

Used Bitzer - Linde compressor pack on a steel frame. Complete with 3x Bitzer 4N-12.2Y semi-hermetic reciprocating compressors, pressure and safety switches/gauges. The compressors have a total displacement of 168,3 m<sup>3</sup>/h. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.



















BITZER KÜHL	MASCH Made in	HINENBAU E.C.	GMBH	Typ 4N- S.Nr. 662		
Nennspannun V 3Ph~	g Frequ Hz	. Betr.strom A (max.)	Anlaufst A (Y)		Fördervol m <sup>3</sup> /h	5 ×
380-420	50	24	69	113	56,10	1450
440-480	60	24	69	113	67,7	1130
IP 54 ND/HD 378 028-05	) max.1	9 /28 bai				

P. L.				1. The		
BITZER KÜHLI	lade in	F.C.			240779	6
Nennspannung V 3Ph~ 380-420 440-480	50 60	24 24	69 69	rom  A (YY) 113 113	Förderve m³/h 56,10 67,7	min <sup>-1</sup> 1450 1750 <b>( (</b>
1440-100 11P 54 ND/HD 378 028-05	max.1	9 /28 bai		- Co.		

		and the second				
<	Bitz	er>			N-12.2 ) 240779	8
BITZER KÜHLMASCHINENBAU GMBH Made in E.C. 682487798 Fördervol Drehzahl						
Nennspannung V 3Ph~	Frequ. Hz	Betr.strom A (max.)	Anlaufst A (Y)	1.1.	m <sup>3</sup> /h 56,10	min <sup>-1</sup>
380-420	50	24	69 69	113	67,7	1750
440-480 IP 54 ND/HD 378 028-05	60 max.19					(6









