

Bitzer HSN 6461-50-40P (x2)

Specifications

Brand	Bitzer
Туре	HSN 6461-50-40P (x2)
Refrigerant	Freon
kW at -20°C/+40°C	165,5
kW at -30°C/+40°C	114,5
kW at -40°C/+40°C	75,0
kW at -45ºC/+40ºC	59,1
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure	/
switches	
Liquid receiver	✓
Liquid receiver ltr.	320
Oil separator	✓
Liquid line filter drier	/
Solenoid Valve	/
m3 / h	330,0
Remarks	Y.o.b. 2007





	condensor and
	evaporators.
Materingahntkisn kg.	₽l523e note: we will only
Package / Rack	øffer this as complete
Sizes	84806re67i0xg292010tirom
	((/៤ix li/V ፍ ងተ)acity matching
Stock	1

Description

Used Bitzer HSN 6461-50-40P (x2)

Used Bitzer HSN 6461-50-40P (x2) semihermetic screw compressors on Freon with a economizer. Complete with a Bitzer F3102N liquid receiver with a volume of 320 liters, Bitzer OA4088 oil separator with a volume of 88 liters, WTT WP 5-70 plate heat exchanger, Grundfos TP 32-230/2 A-F-A-AUUE pump with a Grundfos 80A2-19FT100-C electric motor - Qmax: 6,8 m³/h and Hmax: 16,7 m, pressure and safety switches/gauges, control cabinet with a Mitsubishi FX3u-80M module and 3 Siemens micromaster 420 invert drives. The 2 compressors together have a total displacement of 330 m³/h.

Please note: we will only offer this as complete blastfreezing solution with capacity matching condensor and evaporators.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.



























































