

Carrier 30 RW 080

Specifications

Brand	Carrier
Type	30 RW 080
Product type	Water Cooled Chiller
Capacity kW	80,0
Capacity Tons	22,7
Refrigerant	Freon
Refrigerant Type	R407C
Weight in kg.	761
Sizes	2000x870x1800 mm (LxWxH)
Compressor(s) type & model	2x Performer SZ161T4VC
Display	Carrier Pro-Dialog Plus
Remarks	Y.o.b. 2007
Stock	1



Description

Used Carrier 30 RW 080

Used Carrier 30 RW 080 water cooled chiller on R407C. Complete with 2 Performer SZ161T4VC scroll compressors, plate heat exchanger as condenser with a water volume of 9 liter, plate heat exchanger as evaporator with a water volume of 9 liter and a Carrier Pro-Dialog Plus display.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. if requested we can arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER		12W712823	
2 - MODELE - MODEL MODELLNUMMER		30RW-080-0116-PEE--	
3 - VARIANTE VARIANT VARIANTE		30RW/30RWA	
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSDATUM UND DATUM		12/09/2007	
5 - FLUIDE - - MEDIUM KÄLTEMITTEL		R 407 C	
6 - GROUPE - - GROUP GRUPPE		2	
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B		11.0 Kg / * Kg	
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM		23 --AZOTE--NITROGEN--STICKSTOFF	
10 - PRESSION ADMISSIBLE KIN/MAX ALLOWABLE PRESSURE KIN/MAX ZULÄSSIGE KIN/MAX - DRUCK		(PS) -0.9 / 32.0 bar	22 - BASSE PRESSION LOW PRESSURE NIEDERDRUCKSEITE
11 - TEMPERATURE ADMISSIBLE KIN/MAX ALLOWABLE TEMPERATURE KIN/MAX ZULÄSSIGE KIN/MAX - TEMPERATUREN		(TS) -20.0 / 72.0 °C	-20.0 / 25.0 bar
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK		29.0 bar	* bar
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSENTLÜFT.-SOLLDRUCK		* bar	25.0 bar
14 - PRESSION D'ESSAI D'ETANCHETE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST-DRUCK DES GEBÄTS			15.0 bar
15 - TENSION VOLTAGE SPANNUNG		400 V	16 - PHASES PHASES PHASEN
17 - FREQUENCE FREQUENCY FREQUENZ		~ 50 Hz	3
18 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME		31.5 / * kW	19 - I MAXIMALE MAXIMUM AMP MAXIMAL STROM
20 - POIDS NET NET WEIGHT NETTOGEWICHT		761 Kg	51.6 / * A
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISC SETTING ERSTELLUNGSDRUCK DER BERTSCHHEIBEN		* bar	* bar



