

Bitzer 4H-25.2Y-40P (x3) / 4NCS-12.2Y-40P

Specifications

Brand	Bitzer
Туре	4H-25.2Y-40P (x3) /
	4NCS-12.2Y-40P
Refrigerant	Freon
kW at -5ºC/+40ºC	185,7
kW at -10ºC/+40ºC	152,4
kW at -20ºC/+40ºC	99,0
kW at -30ºC/+40ºC	59,5
kW at -40ºC/+40ºC	31,0
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Oil level system AC&R	✓
Sight Glass	✓
m3 / h	277,1
Remarks	y.o.b. 2011
Package / Rack	✓
Sizes	3800x1600x1430 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4H-25.2Y-40P (x3) / 4NCS-12.2Y-40P

Used Bitzer 4H-25.2Y-40P (x3) / 4NCS-12.2Y-40P reciprocating compressor unit on steel base frame. Complete with an Oilstar oil separator with a volume of 21 liter, oil management system of Emerson, pressure safety switches/gauges and a Swep desuperheater freon/glycol(water). *Why choose for HOSBV2 We are not

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.



Your partner for used commercial and industrial refrigeration equipment







ITZER KÜH	Bits LMASC Made in			S.Nr. 168	25.2Y-40P 0411369	
lennspannung	Frequ.	Betr.strom	Anlaufstron	n	Fördervol.	Drehzahl
/ 3Ph~	Hz	A (max.)	A (Y)	A (YY)	m³/h	min -1
80-420	50	45	116	193	73,7	1450
40-480	60	45	116	193	88,9	1750
02505 ND/HD	max. 1	9 <u>/ 28</u> bai	.			» (







Your partner for used commercial and industrial refrigeration equipment



				srali	annann ceanlithi	
	Bits MASC Made in		S		CS-12.21 0706908	
Nennspannung V 3Ph~	Frequ. Hz	Betr.strom A (max.)	Anlaufstrom A (Y)	A (YY)	Fördervol.	Drehzahl
380-420	50	24,0	69	113	56.2	1450
440-480	60	24,0	69	113	67.9	1750
IP 65 ND/HD m 37802806	iax. 1	9 / 28 bar]		12.44	CE







Your partner for used commercial and industrial refrigeration equipment





