

# Carrier 30 HXC 120

## Specifications

Brand	Carrier
Type	30 HXC 120
Product type	Water Cooled Chiller
Capacity kW	413,0
Capacity Tons	117,4
Refrigerant	Freon
Refrigerant Type	R134A
Weight in kg.	2673
Sizes	3550x960x1890 mm (LxWxH)
Compressor(s) type & model	2x Carrier 06NA2209S7NA-A00
Display	Carrier Pro-Dialog Plus
Stock	1




## Description

### Used Carrier 30 HXC 120

Used Carrier 30 HXC 120 water cooled chiller on R134A. Complete with 2 Carrier 06NA2209S7NC-A00 screw compressors, shell and tube evaporator with a volume of 65 dm<sup>3</sup>, shell and tube evaporator with a volume of 78 dm<sup>3</sup> and a control cabinet with a Carrier Pro-Dialog Plus.

\*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. \*If requested we are happy to arrange your shipment.



N° DE MODELE-MODEL N -TYP.		30HXC120--0006-AEE--	
N° DE SERIE-SERIAL N -FABR Nr.		12C904619	
ANNEE-YEAR-BAUJAHR-		1999	
PRESSION MAX. FONCTION- COTE H.P-MAX. OPERATING PRESS- HIGH SIDE ZULÄSSIGER BETRIEBSÜBERDRUCK - HOCHDRUCKSEITE		28,00 bar	
PRESSION MAX. FONCTION- COTE S.P-MAX. OPERATING PRESS- LOW SIDE ZULÄSSIGER BETRIEBSÜBERDRUCK - NIEDRUCKSEITE		28,00 bar	
FLUIDE - REFRIGERANT - KÄLTEMITTEL		R 134A	
CHARGE CIRCUIT 1 FÜLLMENGES KREISLAUF 1	57,00 kg	CHARGE CIRCUIT 2 FÜLLMENGES KREISLAUF 2	55,00 kg
TENSION VOLTAGE SPANNUNG	400 V	FREQUENCE CYCLES FREQUENZ	50 Hz
1. NOMINALE NOM. AMPS NENNSTROM	184,0 A	PUISSANCE ABSORBEE POWER INPUT LEISTUNGS-AUFNAHME	111,0 kW
POIDS NET NET WEIGHT NETTOWICHT	2673 kg	DRUCKBEH. GRUPPE II/V	
 MANUFACTURED IN FRANCE BY <b>CARRIER s.a.</b> 01120-MONTLUEL-FRANCE <small>A SUBSIDIARY OF CARRIER CORPORATION SYRACUSE NEW YORK UNITED STATES OF AMERICA</small>			





