

Grasso M-3 / MB-3BG

Specifications

| Brand | Grasso |
|---------------------|-------------------------|
| Туре | M-3 / MB-3BG |
| Refrigerant | NH 3 (ammonia) |
| kW at 0°C/+40°C | 637,0* |
| kW at -10°C/+40°C | 350,0** |
| kW at -30°C/+40°C | 165,0*** |
| Electromotor Specs | 50/60 Hz - 132/152 kW - |
| | 2970/3570 RPM |
| Unloaded Start | ✓ |
| Capacity Control | ✓ |
| On steel base frame | 1 |
| Oil separator | ✓ |
| Control panel | ✓ |
| m3 / h | 690,0 |
| Remarks | Y.o.b. 2001 |
| Remarks | Capacity based at: |
| | *(0°C/+35°C) - |
| | **(-15ºC/+35ºC) - |
| | ***(-35°C/+35°C) |
| Sizes | 3050x1200x2200 mm |
| | (LxWxH) |
| Stock | 1 |
| | |



Description

Used Grasso M-3 / MB-3BG

Used Grasso MB-3BG compressor unit on NH3. Complete with 1 Grasso M-3 screw compressor, Schorch KN7280M-AB01B-Z electric motor - 50/60 Hz - 132/152 kW - 2970/3570 RPM, Grasso 250/2000/2 oil cooler, Grasso DM508 oil separator with a volume of 275 liter and a Grasso GSC display. The compressor has a displacement of 690 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also arrange the logistics.































Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment

