

# Bitzer 6G.2

## Specifications

|                          |                            |
|--------------------------|----------------------------|
| Brand                    | Bitzer                     |
| Type                     | 6G.2                       |
| Refrigerant              | Freon                      |
| kW at 0°C/+40°C          | 106,3                      |
| kW at -5°C/+40°C         | 88,0                       |
| kW at -10°C/+40°C        | 72,2                       |
| kW at -20°C/+40°C        | 46,8                       |
| kW at -30°C/+40°C        | 28,5                       |
| kW at -40°C/+40°C        | 15,2                       |
| kW at -45°C/+40°C        | 10,3                       |
| On steel base frame      | ✓                          |
| Pressure safety switches | ✓                          |
| Hp/Lp/Op                 |                            |
| Oil level system AC&R    | ✓                          |
| Solenoid Valve           | ✓                          |
| m3 / h                   | 78,7 - 153                 |
| Sizes                    | 1180x700x670 mm<br>(LxWxH) |
| Stock                    | 1                          |



## Description

### Used Bitzer 6G.2

Used Bitzer 6G.2 open-type reciprocating compressor on Freon. Complete with a Rotor XF180L04 809 electro motor - 50 Hz - 22 kW - 1460 RPM and pressure and safety switches. The compressor has a displacement of 127 m<sup>3</sup>/h at 50 Hz and 153 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.





