

Mycom FM160L-M

Specifications

Brand	Mycom
Type	FM160L-M
Refrigerant	NH 3 (ammonia)
kW at 0°C/+40°C	575,9
kW at -5°C/+40°C	474,8
kW at -10°C/+40°C	387,5
kW at -20°C/+40°C	248,7
kW at -30°C/+40°C	149,8
kW at -40°C/+40°C	81,6
kW at -45°C/+40°C	56,7
Electromotor Specs	50 Hz - 132 kW - 2955 RPM
On steel base frame	✓
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	949
Remarks	Y.o.b. 2013
Package / Rack	✓
Sizes	3600x1200x2400 mm (LxWxH)
Stock	1



Description

Used Mycom FM160L-M

Used Mycom FM160L-M screw compressor unit on R717 (NH3). Complete with Leroy Somer PLS280MP-T - 50 Hz - 132 kW - 2955 RPM, Mycom HS 5023 oil separator with a volume of 465 liter, OWDA CF 220+1400/S oil cooler, Mycom MAA 3066 oil filter, pressure gauges, Grundfos UPS 40-180/2F water pump and a control cabinet with a Mycom MYPRO-CP3 display. The compressor has a displacement of 949 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.









