

# Mycom FM160L-M/A

## Specifications

|                    |                           |
|--------------------|---------------------------|
| Brand              | Mycom                     |
| Type               | FM160L-M/A                |
| Refrigerant        | NH 3 (ammonia)            |
| kW at 0°C/+40°C    | 575,9                     |
| kW at -5°C/+40°C   | 474,8                     |
| kW at -10°C/+40°C  | 387,5                     |
| kW at -20°C/+40°C  | 248,7                     |
| kW at -30°C/+40°C  | 149,8                     |
| kW at -40°C/+40°C  | 81,6                      |
| kW at -45°C/+40°C  | 56,7                      |
| Electromotor Specs | 50 Hz - 132 kW - 2955 RPM |
| Unloaded Start     | ✓                         |
| Capacity Control   | ✓                         |
| Pressure gauges    | ✓                         |
| Hp/Lp/Op           |                           |
| Oil separator      | ✓                         |
| Solenoid Valve     | ✓                         |
| Control panel      | ✓                         |
| Package / Rack     | ✓                         |
| Sizes              | 3600x1200x2400 mm (LxWxH) |



## Description

### Used Mycom FM160L-M/A

Used Mycom FM160L-M/A screw compressor unit on R717 (NH3). Complete with a Leroy Somer electro motor - 50 Hz - 132 kW - 2955 RPM, Mycom HS 5023 oil separator with a volume of 465 liter, OWDA GF 220+1400/S oil cooler, Mycom MAA 3066 oil filter, pressure gauges, Grundfos UPS 40-180/2F water pump and a control cabinet with a Mycom MYPRO-CP3 display.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.











