

Maneurop SZ 100 Condensing unit

Specifications

Brand	Maneurop
Туре	SZ 100 Condensing unit
Refrigerant	Freon
kW at +10ºC/+40ºC	58,8
kW at 0ºC/+40ºC	40,5
kW at -5ºC/+40ºC	33,2
kW at -10ºC/+40ºC	26,8
kW at -20ºC/+40ºC	16,7
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	70
Suction accumulator	 Image: A start of the start of
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	44,2
Condensing Unit	✓
Sizes	2370x910x2200 mm
	(LxWxH)
Stock	1



Description

Used Maneurop SZ 100 Condensing unit

Used Maneurop SZ 100 condensing unit on Freon. Complete with 2 Maneurop SZ 100 scroll compressors, condensor with 2 ATB ABFT71-6B-7RH fans - 50 Hz - 0,18 kW - 880 RPM, Friga-Bohn BSV liquid receiver with a volume of 70 liter, Friga-Bohn suction accumulator, oil separator, pressure and safety switches/gauges and a control panel with a Siemens AC115/120V. The compressors have a total displacement of 44,2 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.







Compressor : Maneurop type SZ 100 Oliesoort : esterolie SZ160 Koudemiddel : R407c 47 kg Filters : zuiggasfilter type : A3F Vloeistoffilter type : H-48 Oliefilter type : F-10B



















FRIGA-BOHN	F - 38460 CREMIEU			Made in France
Mod. BSV 70		Date	06/199	B
N° Série Serial 26 Fabr. Nr. C192137->C19		Régi. Regul. Vorsch.	SDM TUV-RD	
Pression service max.	Côté tube / T Rohrra	ube side	Côté virole	/ Shell side elraum
Max. operat. press./Zul.Betr.Überdr. Température/Temperatur/minmax. Fluide / Fluid / Medium	XXX XXX X ¹ X		33 5ar -10 C/ XXX	





































